



iRAIL - PODS LED System

Lighting Integration for Architectural Railings




VIVA RAILINGS

LEADERS IN ARCHITECTURAL RAILING SYSTEMS

DESIGN • ENGINEER • FABRICATE • INSTALL



iRAIL PODS LED SYSTEM



The LED PODS lighting solution by VIVA Railings delivers seamless and discreet illumination, integrated directly into the handrail system. Designed for both functional and architectural enhancement, each pod provides precision lighting with minimal visual footprint.


Key Features:

- Recessed LED modules housed within stainless steel handrails for a streamlined, minimalist appearance.
- Offers symmetric or 22° asymmetric beam orientation, with beam spreads of 70°, allowing tailored light distribution.
- Multiple spacing options (18", 24", 36") accommodate varying light level requirements along walkways or ramps.
- Delivers 155 lumens per pod, in symmetric or asymmetric setup at just 2W power consumption. .
- Rated IP67, ensuring resistance to dust and water ingress.
- Available in 3000K Warm White or 4000K Cool White color temperatures.

This system is ideal for contemporary environments prioritizing subtle lighting and safety, while maintaining a refined, uninterrupted railing profile.



DETAILS



TOP RAIL / HAND RAIL	FINISH	SPEC
----------------------	--------	------

iRAIL PODS




Ø1-1/2" Stainless steel (304 or 316)	#6 Satin Powder Coated CeraShield PVDF	Color: 3000K Warm White or 4000K Cool White. Output: 2 Watt - 155 lumens per pod Beam Angle: 70° Asymmetrical - 78° Symmetrical Orientation: Symmetrical or Asymmetrical at 22° Power: Input 100 - 305 V AC, Output 12 V DC CRI: >80 Rating: IP67
Ø1-1/2" Stainless steel (201)		
Ø2" Stainless Steel (304 or 316)		
Ø2" Stainless Steel (201)		


Intertek


All LED PODS products are ETL certified;
ETL mark is proof of product compliance to
North American safety standard.



OVERVIEW




iRAIL POD ORIENTATION OPTIONS




iRAIL POD SPACING OPTIONS




DISPERSION DIAGRAM - 18" SPACING



POD RAILING = 36" HEIGHT SYMMETRICAL




POD RAILING = 36" HEIGHT ASYMMETRICAL




Rail Height: 36"
Symmetrical, 18" Spacing

Color	Intensity (ft/cl)
Legend	
	>1ft/cl
	>2ft/cl
	>4ft/cl
	>9ft/cl
	>18ft/cl
	>32ft/cl
	>45ft/cl
	>75ft/cl



POD RAILING = 42" HEIGHT SYMMETRICAL








POD RAILING = 36" HEIGHT ASYMMETRICAL

ALL VALUES IN FOOT-CANDLE (FC)

VIVA RAILINGS IS NOT RESPONSIBLE FOR THE STRUCTURAL INTEGRITY OF ANY BUILDING SYSTEMS OR OTHER MATERIALS NOT FURNISHED BY VIVA RAILINGS. VIVA RAILINGS HAS NO WAY OF KNOWING AND SPECIFICALLY DISCLAIMS WHETHER OR NOT THE BUILDING SYSTEMS TO WHICH VIVA RAILINGS' PRODUCTS ARE TO BE ATTACHED ARE STRUCTURALLY SOUND OR DESIGNED TO PROPERLY SUPPORT VIVA RAILINGS'S MATERIALS. ANY SUCH DESIGN RESPONSIBILITY BELONGS TO OTHERS FOR WHOM VIVA RAILINGS IS NOT RESPONSIBLE. THESE DRAWINGS ARE INTENDED FOR THE SOLE USE OF VIVA RAILINGS' CUSTOMER AND THEIR AGENTS FOR THE INSTALLATION OF PRODUCTS FURNISHED BY VIVA RAILINGS. VIVA RAILINGS REMAINS THE SOLE OWNER OF ALL DESIGNS AND INTELLECTUAL PROPERTY CONTAINED WITHIN. REPRODUCTION AND USE OF THESE DESIGNS FOR ANY OTHER PURPOSE IS FORBIDDEN. SCALES ARE PROVIDED FOR REFERENCE ONLY. FOR PRODUCT INFORMATION AND TECHNICAL SUPPORT, PLEASE CONTACT VIVA RAILINGS.



DISPERSION DIAGRAM - 24" SPACING



Rail Height: 36"
Symmetrical, 24" Spacing


Color	Intensity (ft/cl)
Legend	
	>1ft/cl
	>2ft/cl
	>4ft/cl
	>9ft/cl
	>18ft/cl
	>32ft/cl
	>45ft/cl
	>75ft/cl

ALL VALUES IN FOOT-CANDLE (FC)

VIVA RAILINGS IS NOT RESPONSIBLE FOR THE STRUCTURAL INTEGRITY OF ANY BUILDING SYSTEMS OR OTHER MATERIALS NOT FURNISHED BY VIVA RAILINGS. VIVA RAILINGS HAS NO WAY OF KNOWING AND SPECIFICALLY DISCLAIMS WHETHER OR NOT THE BUILDING SYSTEMS TO WHICH VIVA RAILINGS' PRODUCTS ARE TO BE ATTACHED ARE STRUCTURALLY SOUND OR DESIGNED TO PROPERLY SUPPORT VIVA RAILINGS'S MATERIALS. ANY SUCH DESIGN RESPONSIBILITY BELONGS TO OTHERS FOR WHOM VIVA RAILINGS IS NOT RESPONSIBLE. THESE DRAWINGS ARE INTENDED FOR THE SOLE USE OF VIVA RAILINGS' CUSTOMER AND THEIR AGENTS FOR THE INSTALLATION OF PRODUCTS FURNISHED BY VIVA RAILINGS. VIVA RAILINGS REMAINS THE SOLE OWNER OF ALL DESIGNS AND INTELLECTUAL PROPERTY CONTAINED WITHIN. REPRODUCTION AND USE OF THESE DESIGNS FOR ANY OTHER PURPOSE IS FORBIDDEN. SCALES ARE PROVIDED FOR REFERENCE ONLY. FOR PRODUCT INFORMATION AND TECHNICAL SUPPORT, PLEASE CONTACT VIVA RAILINGS.



DISPERSION DIAGRAM - 36" SPACING




ALL VALUES IN FOOT-CANDLE (FC)

VIVA RAILINGS IS NOT RESPONSIBLE FOR THE STRUCTURAL INTEGRITY OF ANY BUILDING SYSTEMS OR OTHER MATERIALS NOT FURNISHED BY VIVA RAILINGS. VIVA RAILINGS HAS NO WAY OF KNOWING AND SPECIFICALLY DISCLAIMS WHETHER OR NOT THE BUILDING SYSTEMS TO WHICH VIVA RAILINGS' PRODUCTS ARE TO BE ATTACHED ARE STRUCTURALLY SOUND OR DESIGNED TO PROPERLY SUPPORT VIVA RAILINGS'S MATERIALS. ANY SUCH DESIGN RESPONSIBILITY BELONGS TO OTHERS FOR WHOM VIVA RAILINGS IS NOT RESPONSIBLE. THESE DRAWINGS ARE INTENDED FOR THE SOLE USE OF VIVA RAILINGS' CUSTOMER AND THEIR AGENTS FOR THE INSTALLATION OF PRODUCTS FURNISHED BY VIVA RAILINGS. VIVA RAILINGS REMAINS THE SOLE OWNER OF ALL DESIGNS AND INTELLECTUAL PROPERTY CONTAINED WITHIN. REPRODUCTION AND USE OF THESE DESIGNS FOR ANY OTHER PURPOSE IS FORBIDDEN. SCALES ARE PROVIDED FOR REFERENCE ONLY. FOR PRODUCT INFORMATION AND TECHNICAL SUPPORT, PLEASE CONTACT VIVA RAILINGS.




WIRE FEED OPTION



PROVIDE ONE PAIR OF WIRES 14 GA (BLACK-RED) FOR EVERY iRAIL RUN:

- EACH DRIVER FEED SUPPORTS UP TO 70'-0" OR 30 PODS MAX.




*WALL OR FLOOR WIRE FEED ENTRY REQUIRED AT RAILING TERMINAL POINT. TYP.

VIVA RAILINGS IS NOT RESPONSIBLE FOR THE STRUCTURAL INTEGRITY OF ANY BUILDING SYSTEMS OR OTHER MATERIALS NOT FURNISHED BY VIVA RAILINGS. VIVA RAILINGS HAS NO WAY OF KNOWING AND SPECIFICALLY DISCLAIMS WHETHER OR NOT THE BUILDING SYSTEMS TO WHICH VIVA RAILINGS' PRODUCTS ARE TO BE ATTACHED ARE STRUCTURALLY SOUND OR DESIGNED TO PROPERLY SUPPORT VIVA RAILINGS'S MATERIALS. ANY SUCH DESIGN RESPONSIBILITY BELONGS TO OTHERS FOR WHOM VIVA RAILINGS IS NOT RESPONSIBLE. THESE DRAWINGS ARE INTENDED FOR THE SOLE USE OF VIVA RAILINGS' CUSTOMER AND THEIR AGENTS FOR THE INSTALLATION OF PRODUCTS FURNISHED BY VIVA RAILINGS. VIVA RAILINGS REMAINS THE SOLE OWNER OF ALL DESIGNS AND INTELLECTUAL PROPERTY CONTAINED WITHIN. REPRODUCTION AND USE OF THESE DESIGNS FOR ANY OTHER PURPOSE IS FORBIDDEN. SCALES ARE PROVIDED FOR REFERENCE ONLY. FOR PRODUCT INFORMATION AND TECHNICAL SUPPORT, PLEASE CONTACT VIVA RAILINGS.



ORDER CODE



iRAIL LIGHTED RAILING SYSTEM GRANITE PARK VI



GRANITE PARK VI - PLANO, TX

General Contractor: Austin Comm.

Architect: BOKA Powell





VIVA RAILINGS HEADQUARTERS - LEWISVILLE, TX



iRAIL LIGHTED RAILING SYSTEM CHOCTAW CASINO & RESORT



CHOCTAW CASINO & RESORT - DURANT, OK

General Contractor: TEPCO Glass

Architect: JCJ Architecture



iRAIL LIGHTED RAILING SYSTEM ANDRETTI / GRANDSCAPE



ANDRETTI / GRANDSCAPE - THE COLONY, TX

General Contractor: VCC Construction Corp.

Architect: Merriman - MAA Architects





DESIGN + ENGINEER + FABRICATE + INSTALL


151 W. Vista Ridge Mall Dr. Lewisville, TX 75067

(Dallas/Fort Worth Metroplex)

PH: 972.353.8482 | info@vivarailings.com
vivarailings.com



Inc. Magazine 500 | 5000
VIVA RAILINGS, LLC.
Among The Fastest Growing
US Companies
Eight Years in a Row
2012-2019



Inc. Magazine 500 | 5000
VIVA RAILINGS, LLC.
Among The Fastest Growing
Texas Companies
#211



ICC-ES 4405 Certified
SHOE™
Structural Glass Railing System



LEED
Material & Resources Credits 4.1 and 4.2



The American Institute of Architects



The California Contractors State License
Board Certified